

CW

Carton Wrapping Machine



Features and benefits

- AC Drives and Motors – High reliability
- SIGNODE- Powered pre-stretch , Variable up to 300%
- Independent film tension adjustment for wrapping both lighter & heavier cartons
- PLC Controlled with digital display of stretch % and Weight of the film consumed/ Carton
- Convenient operating height
- Top holding attachment for holding the carton while wrapping.



Carton Wrapping Machine

Technical Specifications

MACHINE

Over all dimensions	:	910(W) x 1515(L) x 1630(H)
Machine weight	:	400kgs (max.)

LOAD

Over all dimensions (max.)	:	750(L) x 500(W) x 500 (H)
Over all dimensions (min.)	:	200(L) x 200(W) x 200 (H)(with 10" film width)
Load diagonal	:	910
Weight	:	200 kgs. max.(Centred)

TURN TABLE

Dimensions	:	910diameter with variable speed
Suspension	:	2 nos. Taper roller bearing
Motor	:	0.5 HP, 415 V, 3 Phase
Gear Reducer	:	Worm reducer

Powered Variable Pre-Stretch unit

Stretch	:	variable up 300%
Motor	:	0.5 HP, 415 V, 3 Phase

FILM

Size	:	500 Width x 250 Dia.(max.) x 76 Core Or 250 Width x 250 Dia.(max.) x 76 Core
Elongation	:	Up to 300 %

Note:

- 1)All Dimensions are in mm.
- 2)Carton needs to be turned by 90° for full wrapping
- 3)Optional- Pneumatic up down of the sensor stretch unit to wrap more height of the carton.



E : info@signodeindia.com | W : www.signodegroup.com



Toll Free Number for Services 1800 419 1466